

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Catalyst for Anti-Staining Topcoat

HMIS CODES: H F R P

PRODUCT CODE(S): GBCAT

3 1 1 B

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: R M Car Care, Inc.

ADDRESS: 4401 River Close Blvd.

DATE PRINTED: 1/17/2006

Valrico, FL 33594

NAME OF PREPARER: KL

EMERGENCY PHONE: Chemtrec 800-424-9300

INFORMATION PHONE: 813-294-9223

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	OCCUPATIONAL EXPOSURE LIMITS				VAPOR PRESSURE		WEIGHT %
	CAS NUMBER	OSHA	ACGIH TLV	OTHER1	mm HG @	TEMP (F)	
Polyfunctional x-linker	6426-57-2	N/A	N/A	N/A	N/A		99-100

* Indicates toxic chemical(s) subject to the reporting requirements of Section 313 of Title III and of 40 CFR 372

WARNING: DETECTABLE AMOUNTS OF A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND/OR BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM **MAY** BE PRESENT IN THIS PRODUCT

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING RANGE	<100C	SPECIFIC GRAVITY (H20=1):	1.068
VAPOR DENSITY:	Lighter than air		
EVAPORATION RATE:	Slower than N-Butyl Acetate		
COATING V.O.C.:	0	MATERIAL V.O.C.	0
SOLUBILITY IN WATER:	Soluble		
APPEARANCE AND ODOR:	Opaque, medium viscosity, pourable liquid		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: None determined

FLAMMABILITY LIMITS - LOWER None determined

UPPER: None determined

EXTINGUISHING MEDIA: Water spray, carbon dioxide, chemical foam

SPECIAL FIRE FIGHTING PROCEDURES:

None are expected to be required. If this material is involved in a fire, NIOSH approved self contained breathing apparatus should be worn.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Material can splatter above 100C. This is a water based coating and no fire or explosion hazards are expected.

SECTION V - REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: Excessive heat and freezing temperatures

INCOMPATIBILITY (MATERIALS TO AVOID):

None known to cause dangerous conditions

MATERIAL SAFETY DATA SHEET - Catalyst for Anti-Staining Topcoat

SECTION V - REACTIVITY DATA (continued)

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Carbon monoxide, carbon dioxide, and unidentifiable organic compounds

HAZARDOUS POLYMERIZATION:

Will not occur

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Vapor or mist may cause headaches, nausea, and irritation of nose, throat and lungs.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Contact with skin may be harmful. May cause allergic skin reaction.

SKIN ABSORPTION RISKS AND SYMPTOMS OF EXPOSURE:

May cause allergic skin reaction.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Pain or discomfort in the mouth, chest and abdomen. Nausea, vomiting, diarrhea, dizziness, drowsiness, faintness, weakness and collapse.

HEALTH HAZARDS (ACUTE AND CHRONIC):

Wash hands thoroughly after handling.

CARCINOGENICITY: NTP?: N/A IARC?: N/A OSHA?: N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

N/A

EMERGENCY FIRST AID PROCEDURES:

Inhalation: If vapors are bothersome, remove to fresh air. Skin Contact: Avoid prolonged contact. Wash with large amounts of water. If irritation persists, see physician. Eye Contact: Flush with large amounts of water until all material is removed. If irritation persists, get medical attention immediately. Ingestion: Consult physician.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Confine as much as possible. Dike and absorb with inert material such as vermiculite. Transfer to containers for disposal.

MATERIAL SAFETY DATA SHEET - Catalyst for Anti-Staining Topcoat

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE (continued)

WASTE DISPOSAL METHOD:

Dispose of waste in accordance with Federal, State, and Local ordinances.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Wear gloves, goggles and protective clothing to prevent contact with product. Store material at room temperatures between 49C (120F) and 2C (36F) Do not store containers in direct sunlight.

OTHER PRECAUTIONS:

N/A

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION:

Wear respirator during spray application

VENTILATION:

Adequate to keep exposure limits below those listed in SECTION II

PROTECTIVE GLOVES:

Impervious rubber gloves.

EYE PROTECTION:

Chemical splash goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Wear protective clothing to prevent contact with this product.

WORK / HYGENIC PRACTICES:

N/A

SECTION IX - TRANSPORTATION AND SHIPPING

DOT/UN SHIPPING NAME:

FREIGHT DESCRIPTION

DOT/UN CLASS:

NA/UN NUMBER:

PACKING GROUP:

DOT LABELS REQUIRED

SECTION IX - DISCLAIMER

R M Car Care urges each customer or recipient of this MSDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this MSDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Since conditions for the use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product.