

MATERIAL SAFETY DATA SHEET

(MSDS)

Identity (As used on label or container): **GatorBack Gum Remover**

EMERGENCY MEDICAL TELEPHONE NUMBER (24 HOUR ASSISTANCE) 1-800-228-5635

PRODUCT HAZARD RATINGS: Health=1, Fire=3, Reactivity=1, Protective Equipment=1

(Rating Legend: 4=Extreme, 3=Serious, 2=Moderate, 1=Slight, 0=Minimal)

SECTION 1

R&M Car Care, Inc.
4401 River Close Blvd.
Valrico, FL 33596

Date Prepared: 08/30/03
Name of Preparer; Ron J. Smyntek

Section 2 – Hazardous Ingredients / Identity Information

Chemical Names	Exposure Limits	SARA Title 3	ACGIH	OSHA	% By Weight
CAS Number	(LD50-Oral Rat)	SEC 313	TLV/TWA	PEL	

Xylene 1330-20-7	ND	Yes	100 ppm	100 ppm	40-50
------------------	----	-----	---------	---------	-------

Aliphatic Petroleum

Distillates 54742-89-8	ND	No	300 ppm	300 ppm	40-50
------------------------	----	----	---------	---------	-------

Ethyl Benzene 100-41-4	800 mg/kg	Yes	100ppm	100ppm	0-5
------------------------	-----------	-----	--------	--------	-----

Components listed as a Suspected carcinogen; None

SECTION 3 – PHYSICAL CHARACTERISTICS

Boiling Point: >280F Vapor Pressure: (psig): 21.0 Specific Gravity (H2O=1): .86

Solubility/Water: NIL Vapor Density (AIR=1): 3.70 Evaporation Rate (Ether=1): 1.20

pH @ 100%: Aqueous pH @ 1%: approx ND

Appearance and Odor; Clear liquis, mild chemical odor

SECTION 4 – Fire and Explosion Hazard Data

Flash Point: 100F

Flammable Limits: LEL: 1.0 UEL 7.0

Extinguishing Media: Water, Fog, Foam Dry Chemical, Sand, Earth satisfactory

Special Fire Fighting Procedures: NA

Unusual Fire and Explosion Hazards: Product may produce a floating fire.

SECTION 5 – REACTIVITY DATA

Stability: Stable

Hazardous Polymerization: Will not occur

Incompatibility (Materials to Avoid): Bleaching Agents and Oxidizers

Hazardous Decomposition Products: Carbon Monoxide

Conditions to Avoid: Heat, Static Electricity, Sparks and Flames